

# HEG High Volume Wash Series

# ERIE PRO

POWER CLEANING & EQUIPMENT

Equipped with all the same great features you come to expect but with the high volume wash and natural gas/LP features built in. This is an excellent choice for applications that require the removal of heavy mud and solids.

## Natural Gas/LP Belt Drive

- Belt drive triplex piston ceramic plunger General pump
  - Easy-to-access control panel
  - Polyethylene float tank (8-gallon with in-line filter)
  - 1/2-inch schedule 80 coil heat exchanger with 8 pancake design (3/4-inch on HEG-2010)
  - Time delay shutdown
  - Detergent valve
  - On/Off pump/motor switch
  - On/Off burner switch
  - Adjustable outlet thermostat for main temperature control
- Note: Draft diverter not included



HEG-3008-1E3G

### Additional Features:

#### Pump

- Thermal relief valve

#### Motor

- Open drip-proof electric motor with thermal overload protection

#### Frame

- Powder coated steel frame with removable side panels

#### Components

- Natural gas or LP gas-fired (Vapor only) natural draft with aspirating-type burner, 12-inch stack
- 24V control system
- Electronic ignition with intermittent pilot

#### Miscellaneous

- Temperature rise 150°F/66°C above ambient, maximum outlet temperature is 200°F

#### Unit Includes:

- Quick connect nozzles – 0°, 15°, 25° & 40°
- 50-foot x 3/8-inch steel wire-braided pressure hose with swivel and bend restrictors (1/2-inch on HEG-2010)
- Professional-grade insulated trigger gun with safety lock-off
- Adjustable pressure insulated dual lance with fixed detergent nozzle

### NATURAL GAS INSTALLATION RECOMMENDATION:

This natural gas pressure washer must have a clearance of 2-feet on all sides of the unit and 4-feet above the unit.

#### Gas Supply Line:

##### Natural Gas

7- to 8-inch water column input

##### LP Gas

12- to 14-inch water column input

### Recommended Pipe Sizes for Gas Supply Line:

#### Natural Gas

Distance to Unit from Regulator	Pipe Size
0-feet to 50-feet	1½-inch 1PS
50-feet to 100-feet	2-inch 1PS
100-feet to 200-feet	2½-inch 1PS

#### LP Gas

Distance to Unit from Regulator	Pipe Size
0-feet to 50-feet	1½-inch 1PS
50-feet to 100-feet	1½-inch 1PS
100-feet to 200-feet	1¾-inch 1PS

# HEG High Volume Wash Series

# ERIE PRO

POWER CLEANING & EQUIPMENT

Model Number	PSI	GPM	Horsepower/Motor	Natural Gas BTU per hour	LP Gas BTU per hour	Dimensions (LxWxH)	Ship Wt.	Net Wt.
HEG-2010-1E3G	2000	9.9	15.0 HP, 230V, 3Ø, 39.0A	768,000	730,000	78.5x34.75x65.75in.	1570 lb.	1420 lb.
HEG-2010-1E4G	2000	9.9	15.0 HP, 460V, 3Ø, 19.2A	768,000	730,000	78.5x34.75x65.75in.	1570 lb.	1420 lb.
HEG-2010-1E5G	2000	9.9	15.0 HP, 575V, 3Ø, 15.4A	768,000	730,000	78.5x34.75x65.75in.	1539 lb.	1389 lb.
HEG-2010-1E9G	2000	9.9	15.0 HP, 208V, 3Ø, 42.5A	768,000	730,000	78.5x34.75x65.75in.	1553 lb.	1403 lb.
HEG-3008-1E3G	3000	7.8	15.0 HP, 230V, 3Ø, 39.0A	650,000	619,500	70x34.75x54.5in.	1207 lb.	1057 lb.
HEG-3008-1E4G	3000	7.8	15.0 HP, 460V, 3Ø, 19.2A	650,000	619,500	70x34.75x54.5in.	1207 lb.	1057 lb.
HEG-3008-1E5G	3000	7.8	15.0 HP, 575V, 3Ø, 15.4A	650,000	619,500	70x34.75x54.5in.	1176 lb.	1026 lb.
HEG-3008-1E9G	3000	7.8	15.0 HP, 208V, 3Ø, 42.5A	650,000	619,500	70x34.75x54.5in.	1190 lb.	1040 lb.

### Options:

Part Number	Description	Fits Models
HX-0180	Liquid propane (Vapor only) - Converts natural gas pressure washer to operate on liquid propane (vapor only)	HEG-3008 models
HX-0181	Auto start/stop - When trigger gun is released timer will turn unit off; when trigger gun is pulled, unit will restart	All models
HX-0182 *	(1) Remote station - Adds control box which may be mounted away from unit to control on/off, burner and soap injection	All models
HX-0183	Additional remotes (up to 3) - Additional remotes that may be added to the unit after the first remote is installed	All models
HX-0187	Stainless-steel access panels - Converts powder coated painted access panels to stainless-steel material	HEG-3008 models
HX-0188	Stainless-steel coil wrap - Converts powder coated painted coil wrap to stainless-steel material	HEG-3008 models
HX-0189	Liquid propane (Vapor only) - Converts natural gas pressure washer to operate on liquid propane (vapor only)	HEG-2010 models
HX-0193	Stainless-steel access panels - Converts powder coated painted access panels to stainless-steel material	HEG-2010 models
HX-0194	Stainless-steel coil wrap - Converts powder coated painted coil wrap to stainless-steel material	HEG-2010 models
HX-0267	Balanced temperature control - Thermostat in heating coil anticipates spiking temperature and cycles the burner to maintain steady outlet temperatures	HEG-3008 models
HX-0268	Balanced temperature control - Thermostat in heating coil anticipates spiking temperature and cycles the burner to maintain steady outlet temperatures	HEG-2010 models
HX-0269	Dual gun - Two guns may be sprayed at the same time, flow is divided between the two guns while each operator maintains equal system pressure; includes balanced temperature control option HX-0267	HEG-3008 models
HX-0270	Dual gun - Two guns may be sprayed at the same time, flow is divided between the two guns while each operator maintains equal system pressure; includes balanced temperature control option HX-0268	HEG-2010 models

### Accessory:

Part Number	Description	Fits Models
50-0186	Draft diverter, 12-inch - For use during installation. Prevents backdrafts through the flue.	All models



\*HX-0182  
Optional Remote Station

